



Applications

- Industrial lighting
- Warehouses
- Amenity lighting
- Parking lots
- Foundries
- Assembly Shops

Features

- High energy savings
- High lumen efficiency
- Longer life (up to 20,000 hrs.)
- Retrofit versions for HPS / HPMV lamps
- Better cold starting
- UV Shield available

Open Rated Lamps

Description	Part Code	Initial Lumens*	Avg. Life Hours*	Colour Temp.	CRI	LPW	Burn Position	Operating Current (A)	Carton Qty.	Control Gear	Base
HIPE 70 W/C/U/LU/UVS/737	10003	5000	15000	3700	70	71	Universal	0.90	12	MH / HPSV	E27
HIPE 70 W/C/U/LU/UVS/732	52910	5000	15000	3200	70	71	Universal	0.90	12	MH / HPSV	E27
HIPE 150 W/C/U/LU/UVS/737	10007	12600	15000	3700	70	84	Universal	1.80	12	MH / HPSV	E27
HIPE 150 W/C/U/LU/UVS/740	10006	13300	15000	4000	68	89	Universal	1.80	12	MH / HPSV	E27

Description	Part Code	Initial Lumens*	Avg. Life Hours*	Colour Temp.	CRI	LPW	Burn Position	Lamp Op. Cur. (A)	Carton Qty.	Control Gear	Base
HIPE 150 W/C/U/LU/E90/UVS/737	10082	12600	15000	3700	70	84	Universal	1.80	12	MH / HPSV	E40
HIPE 150 W/U/LU/E90/UVS/740	10051	13300	15000	4000	68	89	Universal	1.80	12	MH / HPSV	E40
HIPE 250 W/C/HBU/LU/UVS/737	10076	20000	20000	3700	70	80	Base Up ± 90*	3.10	12	MH / HPSV	E40
HIPE 250 W/C/V/UVS/PS/737	10014	23000	20000	3700	70	92	Base Up ± 15*	2.10	12	MH / HPMV	E40
HIPE 400 W/C/V/LU/UVS/737	10043	40000	20000	3700	70	100	Base Up ± 15*	4.00	6	MH / HPSV	E40
HIPE 400 W/C/V/UVS/EL/PS/737	10041	40000	30000	3700	70	100	Base Up ± 15*	3.20	6	MH / HPMV	E40
HIPE 400 W/ V/LU/UVS/740	10077	42000	20000	4000	68	95	Base Up ± 15*	4.00	6	MH / HPSV	E40

Clear Lamps are available upon request

* When operated in vertical burn position