



Applications

- Down lighting
- Accent lighting
- Wall sconce
- Track lighting

Features

- Compact configuration
- Precise optical control
- Excellent colour uniformity
- Uni-Form™ formed body arc tube

Description	Part Code	Initial Lumens*	Avg. Life Hours*	Colour Temp.	CRI	LPW	Burn Position	Operating Current (A)	Carton Qty.	Control Gear
HIT 70 W/G12/UVS/3K	12108	5600	10000	3000	70	75	Universal	0.90	25	MH / HPSV
HIT 70 W/G12/UVS/4K	52983	5600	10000	4200	70	75	Universal	0.90	25	MH / HPSV
HIT 70 W/G12/UVS/6K	39682	4800	5000	6500	90	64	Universal	0.90	25	MH / HPSV
HIT 100 W/G12/UVS/4K	89887	9000	10000	4200	70	90	Universal	1.10	25	MH
HIT 150 W/G12/UVS/3K	12106	14000	10000	3000	70	93	Universal	1.80	25	MH / HPSV
HIT 150 W/G12/UVS/4K	25779	14000	10000	4200	70	93	Universal	1.80	25	MH / HPSV
HIT 150 W/G12/UVS/FS/6K	78564	11250	5000	6500	90	75	Universal	1.80	25	MH / HPSV

* When operated in vertical burn position